



# Aguapure Compact

## General

Indication	Aguapure Compact
Power supply (V) at 50 Hz	240
Frequency (Hz)	50
Consumption (Kw)	0,20
Protection class	IP 65
Fuse in device (A)	16A
Contact load, relay (VA)	1000, max. 250V bij 4A
Salt tank volume (L)	10
Water tank volume (L)	35
Device dimensions W x H x D (mm)	530 x 550 x 200
Controller dimensions W x H x D (mm)	300 x 230 x 130
Weight (kg)	20

## Chlorine gas regulation

Indication	Setting ranges	Factory settings
Alarm value above (mg/l)	0 – 10,00	0,80
Warning value above (mg/l)	0 – 10,00	0,80
Nominal value chlorine (mg/l)	0 – 10,00	0,50
Warning value below (mg/l)	0 – 10,00	0,25
Alarm delay (min)	0 – 15	2

## pH control

Indication	Setting ranges	Factory settings
Alarm value above (pH)	3,00 – 12,00	7,20
Warning value above (pH)	3,00 – 12,00	7,60
Nominal value (pH)	3,00 – 12,00	7,30
Alarm value below (pH)	3,00 – 12,00	6,80
Warning value below (pH)	3,00 – 12,00	6,80
Warning value under Alarm delay (sec)	0 – 15	2